

VELCRO® Brand

# ALFA-LOK® Fastener with SilverTape® 5310 Adhesive Transparent

**NEW**




## Features

- Free positionable, re-closable fastening system
- High Performance double sided acrylic foam tape
- Suitable for high surface energy material such as glass and treated plastics

## Compatibility Surfaces

SUBSTRATES	VELCRO® Brand ALFA-LOK® Fastener
GLASS	+
ALUMINUM (ANODIZED, RAW)	+
STEEL (STAINLESS, GALVANIZED)	+
PLYWOOD/MDF	+* (1)
FORMICA (POLISHING SIDE)	-
CARDBOARD	-
PAINTED WALLBOARD	+* (1)
CONCRETE	+* (1)
STONE	+* (1)
ABS	-
POLYESTER	-
VINYL	-
POLYACRYLIC/PMMA	-
POLYCARBONATE	-
POLYETHYLENE	-
POLYPROPYLENE	-
FABRICS	-

## Performance Specifications

Testing	Minimum Value
<b>BASE MATERIAL</b>	Modified Solvent based Acrylic Polymer
<b>ADHESIVE COLOUR</b>	Transparent
 °C <b>TEMPERATURE RANGE OF USE</b>	Long Term: From -40 °C to +100 °C Short Term: 160 °C
 <b>PEEL 180° ADHESION (FINAT-FTM 01) (AVERAGE)</b>	11 N/cm * 16 N/cm * - (after 24 h)
<b>SOFTENING POINT</b>	100 °C
 <b>STATIC SHEAR (ASTM 3654)**</b>	1,000 gr. at 22 °C 500 gr. at 66 & 93 °C
<b>TACK</b>	Medium/Low
<b>APPLICATION METHOD</b>	Pressure
<b>APPLICATION</b>	High surface energy, highly transparent bond

\* Average according typical values.

The specifications are as a reference and are pending to confirm.

\*\* Weight that ½ square inch will hold 10,000 minutes (7 days).



- Not Recommended   
 + Recommended   
 +\* (1) Recommended with AFTC 101 Primer




**PRODUCT USE.** The information, statements and comments contained within this document are based on our experience and testing and are believed to be accurate. However, because there are many factors involved in specific applications that can impact end use and performance, product users should always test the product for its ability to meet the requirements of their specific use and method of application.

VELCRO® Brand

## ALFA-LOK® Fastener Closure Characteristics



### SELF-ENGAGING MUSHROOM

CHARACTERISTICS	VELCRO® Brand ALFA-LOK® Tape
<b>DENSITY</b>	48 heads/cm <sup>2</sup>
<b>CONSTRUCTION</b>	Woven quadrilobal mushroom tape
<b>BASE MATERIAL</b>	<b>Base:</b> Polyester
	<b>Mushrooms:</b> Polypropylene
<b>FASTENER</b>	Self-engaging
<b>CYCLE LIFE</b>	-
 <b>PEEL STRENGTH (AVERAGE)</b>	2 N/cm
 <b>SHEAR STRENGTH (AVERAGE)</b>	50 N/cm <sup>2</sup>
 <b>TENSILE DISENGAGEMENT (AVERAGE)</b>	40 N/cm <sup>2</sup>
<b>STANDARD COLOURS</b>	Black
<b>STANDARD WIDTHS</b>	25mm
<b>STANDARD PUT-UPS</b>	25m rolls with flanges
	Cut pieces (customized)



### GLOBAL OFFICES

#### Global Corporate Headquarters

Velcro USA Inc.  
95 Sundial Avenue  
Manchester, NH 03103  
USA  
Tel: (+1) 800 225 0180  
marketing@velcro.com  
Velcro.com

### NAM

#### USA

Velcro USA Inc.  
Tel: (+1) 800 225 0180  
marketing@velcro.com  
Velcro.com

#### Canada

Velcro Canada Inc.  
Tel: (+1) 800 683 5276  
canada@velcro.com  
Velcro.com

### LATAM

#### Mexico

Velcro de México, S.A. de C.V.  
Tlalnepantla de Baz,  
Edo. de México  
Tel: (+52) 55 5005 3300  
infovdmex@velcro.com  
Velcrodemexico.com

León, Gto  
Tel: (+52) 477 980 0630  
infovdmex@velcro.com  
Velcrodemexico.com

#### Brazil

Velcro Brasil Importação,  
Exportação e Comércio de  
Sistemas de Fixação Ltda.

Campo Bom, RS  
Tel: (+55) 51 3599 1483  
infovbra@velcro.com  
Velcro.com.br

Sumaré, SP  
Tel: (+55) 11 3197 2588  
infovbra@velcro.com  
Velcro.com.br

#### Uruguay

Velcroindustrial  
del Uruguay S.A.  
Tel: (+598) 2288 0008  
infovurg@velcro.com  
Velcro.com

### EMEA

#### Spain

Velcro Europe S.A.  
Tel: (+34) 93 758 32 98  
infovesa@velcro.com  
Velcro.es

#### Germany

Velcro GmbH  
Freiberg am Neckar  
Tel: (+49) 7141 991 19-0  
infovgmbh@velcro.com  
Velcro.de

Gronau  
Tel: (+49) 2562 96 45-0  
infovgmbh@velcro.com  
Velcro.de

#### France

Velcro Industries France S.A.S.  
Tel: (+33) 1 34 38 78 88  
infovif@velcro.com  
Velcro.fr

#### Belgium

Alfatex N.V.  
Tel: (+32) 9 386 12 18  
infofbe@velcro.com  
Velcro.be

#### Italy

Velcro Italia, S.R.L.  
Tel: (+39) 039 62 70 01  
infoveit@velcro.com  
Velcro.it

#### UK

Velcro Ltd.  
Tel: (+44) 1606 738 806  
infovlt@velcro.com  
Velcro.co.uk

#### Poland

Velcro Poland Sp. z o.o.  
Tel: (+48) 71 798 57 89  
infovpl@velcro.com  
Velcro.pl

### APAC

#### Australia

Velcro Australia Pty. Ltd.  
Tel: (+61) 3 9703 2466  
infovaus@velcro.com  
Velcro.com.au

#### China

Velcro China Fastening  
Systems Company Limited  
Tel: (+86) 21 6045 2090  
(Shanghai Sales Office)  
infovch@velcro.com  
Velcro.com.cn

#### Hong Kong

Velcro Hong Kong Ltd.  
Tel: (+852) 2570 3698  
infovhk@velcro.com  
Velcro.com.hk  
Velcro.kr

#### Vietnam

Velcro Vietnam Company Limited  
Tel: (+84) 274 2222 497  
infovn@velcro.com  
Velcro.vn